



**PARTS LIST**

ITEM	DESCRIPTION	MATERIAL
1.	BODY	CAST IRON, ASTM A126-B
2.	COVER	CAST IRON, ASTM A126-B
3.	SEAT	BUNA-N & 304 STAINLESS STEEL
4.	COVER BOLTS	ZINC PLATED STEEL (Standard)
		316 STAINLESS STEEL (Optional)
5.	COVER NUTS	ZINC PLATED STEEL (Standard)
		316 STAINLESS STEEL (Optional)
6.	REDUCING BUSHING *	STEEL
7.	PIPE PLUG	STEEL
8.	FLOAT BALL	316 STAINLESS STEEL
9.	FLOAT GUIDE	ULTRA HIGH MOLECULAR WEIGHT POLYETHYLENE
10.	CUSHION	BUNA-N RUBBER
11.	GUIDE BEARING	SELF LUBRICATING POLYMER
12.	PIPE PLUG	STEEL

\* Part #6 reducing bushing used in 1/2" and 3/4" sizes only

FIGURE NUMBER	MAXIMUM WORKING PRESSURE	HYDRO TEST PRESSURE
<b>930-T</b>	300 PSI (2,068 KPa)	450 PSI (3,103 KPa)

FIGURE 930 AIR & VACUUM VALVES ARE MANUFACTURED AND TESTED IN ACCORDANCE WITH AWWA C512

SIZE	INLET	OUTLET	A	B	WGT
1/2" (DN15)	1/2" NPT	1/2" NPT	3.88" (98mm)	7.13" (181mm)	10 lbs (4.5 kg)
3/4" (DN20)	3/4" NPT	3/4" NPT	3.88" (98mm)	7.13" (181mm)	10 lbs (4.5 kg)
1" (DN25)	1" NPT	1" NPT	3.88" (98mm)	7.13" (181mm)	10 lbs (4.5 kg)

<b>GA INDUSTRIES, a VAG Brand</b>		
DATE: 8-23-08	DRAWN BY: WJN	
<b>1/2", 3/4" &amp; 1" KINETIC AIR &amp; VACUUM VALVE</b>		
<b>FIGURE 930-T</b>	DRAWING NO. <b>EAV-7051-W</b>	REV <b>A</b>