

FIGURE 945 COMBINATION AIR VALVES ARE MANUFA	CTURED
AND TESTED IN ACCORDANCE WITH AWWA C5	12

FIGURE NUMBER	MAX WORKING PRESSURE	AIR RELEASE ORIFICE	INLET	OUTLET	A (Length)	B (Height)	C (Width)	WGT	
945	150 PSI (1034 KPa)	3/16" (3,2mm)	· 3" NPT	3" NPT	3" NPT	12.75"	12.25"	6.63"	65 lbs
945-H	300 PSI (2068 KPa)	1/8" (2,4mm)			3 NPT 3	3 NP1	(324mm)	(311mm)	(168mm)

PARTS LIST				
ITEM	DESCRIPTION	MATERIAL		
1.	BODY	CAST IRON, ASTM A126-B		
2.	COVER	CAST IRON, ASTM A126-B		
3.	SEAT	BUNA-N RUBBER		
4.	SEAT SCREWS	18-8 STAINLESS STEEL		
5.	FLOAT BALL (Air Vacuum)	316 STAINLESS STEEL		
6	00/50 00/50	ZINC PLATED STEEL (Standard)		
6.	COVER BOLTS	316 STAINLESS STEEL (Optional)		
7.	PIPE PLUG	STEEL		
8.	ORIFICE BUTTON	BUNA-N & 18-8 STAINLESS		
9.	ORIFICE	316 STAINLESS STEEL		
10.	FLOAT BALL (Air Release)	316 STAINLESS STEEL		
11.	LEVERAGE ARM	316 STAINLESS STEEL		
12.	FLOAT ARM	316 STAINLESS STEEL		
13.	AIR RELEASE VALVE LINK	18-8 STAINLESS STEEL		
14.	HEX NUT	18-8 STAINLESS STEEL		
15.	SPRING PIN	302 STAINLESS STEEL		
16.	LEVERAGE BRACKET	316 STAINLESS STEEL		
17.	BRACKET SCREWS	18-8 STAINLESS STEEL		
18.	FLOAT PIVOT LINK	316 STAINLESS STEEL		
19.	FLOAT SCREW	18-8 STAINLESS STEEL		
20.	COVER GASKET	ARMSTRONG CS-301		
21.	BRACKET LOCK WASHER	18-8 STAINLESS STEEL		
22.	LOCK WASHER	18-8 STAINLESS STEEL		
23.	CUSHION	BUNA-N RUBBER		
24.	FLOAT GUIDE	UHMWPE		
25.	GUIDE BEARING	SELF-LUBRICATING POLYMER		

GA INDUSTRIES, a VAG Brand						
DATE:	9-5-08	DRAWN BY: WJN				
3" COMPACT KINETIC COMBINATION AIR VALVE						
FIGURE 945 PRAWING NO. ECAV-7138-W				REV		