



PARTS LIST		
PART	DESCRIPTION	MATERIAL
1	BODY	CAST IRON, ASTM A126 CL B*
2	COVER	CAST IRON, ASTM A126 CL B*
3	LEVERAGE BRACKET	316 STAINLESS STEEL
4	HEX HEAD CAP SCREW	304 STAINLESS STEEL
5	ORIFICE	316 STAINLESS STEEL
6	ORIFICE BUTTON SEAL	BUNA-N RUBBER
7	ORIFICE BUTTON SCREW	304 STAINLESS STEEL
8	LOCK NUT	304 STAINLESS STEEL
9	LOCK WASHER (2)	304 STAINLESS STEEL
10	SPRING PIN (6)	302 STAINLESS STEEL
11	LEVER ARM	316 STAINLESS STEEL
12	FLOAT ARM	316 STAINLESS STEEL
13	LINK	316 STAINLESS STEEL
14	UNIVERSAL COUPLING	316 STAINLESS STEEL
15	FLOAT ROD	316 STAINLESS STEEL
16	FLOAT BALL	316 STAINLESS STEEL
17	COVER SEAL	BUNA-N RUBBER
18	PIPE PLUG 1/2"	STEEL
19	PIPE PLUG 1"	MALLEABLE IRON
20	PIPE PLUG 2"	MALLEABLE IRON
21	FLOAT HOOD	316 STAINLESS STEEL
22	FLOAT SCREW	304 STAINLESS STEEL
23	ORIFICE BUTTON	316 STAINLESS STEEL
24	COVER BOLTS (4) (NOT SHOWN)	A307 ZINC PLATED STEEL (OPTIONAL 316 STAINLESS STEEL)
25	ORIFICE BUTTON WASHER	304 STAINLESS STEEL

* LINED AND COATED WITH NSF-61 CERTIFIED EPOXY

FIGURE NUMBER	INLET	OUTLET	ORIFICE DIAMETER	WORKING PRESSURE	PRESSURE RATING	HYDRO TEST PRESSURE
923-D	6" ANSI B16.1 CLASS 125	1" NPT	1.000"	10 - 150 PSI	300 PSI	450 PSI
923H-D	6" ANSI B16.1 CLASS 125	1" NPT	0.688"	10 - 200 PSI		
923H-U	6" ANSI B16.1 CLASS 250	1" NPT	0.688"	10 - 300 PSI		

FIGURE 923 AIR RELEASE VALVES ARE MANUFACTURED AND TESTED IN ACCORDANCE WITH AWWA C512

GA INDUSTRIES a +GF+ Brand

DATE: 6-2-26 DRAWN BY: WJN

6" SUPER HIGH-CAPACITY AIR RELEASE VALVE

FIGURE 923 DRAWING NO. **EAR-7030W** REV **A**