



### PARTS LIST

ITEM	DESCRIPTION	MATERIAL
1.	BODY	CAST IRON, ASTM A126-B*
2.	COVER	CAST IRON, ASTM A126-B*
3.	LEVERAGE BRACKET	316 STAINLESS STEEL
4.	BRACKET SCREW	18-8 STAINLESS STEEL
5.	LEVER ARM	316 STAINLESS STEEL
6.	FLOAT ARM	316 STAINLESS STEEL
7.	ORIFICE BUTTON	BUNA-N / 18-8 STAINLESS STEEL
8.	HEX NUT	18-8 STAINLESS STEEL
9.	LOCK WASHER	18-8 STAINLESS STEEL
10.	SPRING PIN	302 STAINLESS STEEL
11.	AIR RELEASE VALVE LINK	316 STAINLESS STEEL
12.	PIVOT LINK	316 STAINLESS STEEL
13.	FLOAT CAP SCREW	18-8 STAINLESS STEEL
14.	BRACKET LOCK WASHER	18-8 STAINLESS STEEL
15.	FLOAT BALL	316 STAINLESS STEEL
16.	COVER BOLTS	ASTM A307 ZINC PLATED STEEL (OPTIONAL 316SS)
17.	COVER NUTS	ASTM A307 ZINC PLATED STEEL (OPTIONAL 316SS)
18.	PIPE PLUG, 1/2"	STEEL
19.	PIPE PLUG, 1"	MALLEABLE IRON
20.	ORIFICE	316 STAINLESS STEEL
21.	O-RING	BUNA-N RUBBER

\* LINED AND COATED WITH NSF-61 CERTIFIED EPOXY

FIGURE 920 AIR RELEASE VALVES ARE MANUFACTURED AND TESTED IN ACCORDANCE WITH AWWA C512

FIGURE NUMBER	ORIFICE DIAMETER	WORKING PRESSURE	PRESSURE RATING	WEIGHT
920	3/16"	10-150 PSI	300 PSI	24 LBS.
920-H	1/8"	10-300 PSI		

<b>GA INDUSTRIES</b> a +GF+ Brand		
DATE: 9-06-08	DRAWN BY: WJN	
<b>COMPOUND LEVER AIR RELEASE VALVE</b>		
<b>FIGURES 920,920H</b>		DRAWING NO. <b>EAR-7003-W</b> REV <b>A</b>