



PARTS LIST

ITEM	DESCRIPTION	MATERIAL
1.	BODY	316 STAINLESS STEEL
2.	COVER	316 STAINLESS STEEL
3.	LEVERAGE BRACKET	316 STAINLESS STEEL
4.	ORIFICE	316 STAINLESS STEEL
5.	LEVERAGE BRACKET SCREWS	18-8 STAINLESS STEEL
6.	BRACKET LOCK WASHER	18-8 STAINLESS STEEL
7.	ORIFICE BUTTON	BUNA-N / 18-8 STAINLESS STEEL
8.	HEX NUT	18-8 STAINLESS STEEL
9.	LOCK WASHER	410 STAINLESS STEEL
10.	O-RING	BUNA-N RUBBER
11.	LEVER ARM	316 STAINLESS STEEL
12.	FLOAT ARM	316 STAINLESS STEEL
13.	SPRING PIN	316 STAINLESS STEEL
14.	VALVE LINK	316 STAINLESS STEEL
15.	FLOAT PIVOT LINK	316 STAINLESS STEEL
16.	COVER BOLTS	316 STAINLESS STEEL
17.	PIPE PLUG, 1/2"	316 STAINLESS STEEL
18.	FLOAT ROD	316 STAINLESS STEEL
19.	FLOAT BALL	316 STAINLESS STEEL
20.	PIPE PLUG, 1"	316 STAINLESS STEEL
21.	PIPE PLUG, 2"	316 STAINLESS STEEL

INLET	OUTLET	A	B	C	WGT
2" NPT	1/2" NPT	6.38" (162mm)	20.50" (521mm)	4.50" (114mm)	60 lbs (27,3 kg)

FIGURE NUMBER	ORIFICE DIAMETER	WORKING PRESSURE
925SSL	5/16" (7,9mm)	10-75 PSI (69-517KPa)
925SS	3/16" (4,8mm)	10-150 PSI (69-1034KPa)

GA INDUSTRIES *a +GF+ Brand*

DATE: 8-23-08	DRAWN BY: WJN
DUROVENT™ ALL STAINLESS STEEL SEWAGE AIR RELEASE VALVE	
FIGURE 925SS	DRAWING NO. EAR-7008SW
	REV A