



**PARTS LIST**

ITEM	DESCRIPTION	MATERIAL
1.	BODY	316 STAINLESS STEEL
2.	COVER	316 STAINLESS STEEL
3.	LEVERAGE BRACKET	316 STAINLESS STEEL
4.	ORIFICE	316 STAINLESS STEEL
5.	LEVERAGE BRACKET SCREWS	18-8 STAINLESS STEEL
6.	BRACKET LOCK WASHER	18-8 STAINLESS STEEL
7.	ORIFICE BUTTON	BUNA-N / 18-8 STAINLESS STEEL
8.	HEX NUT	18-8 STAINLESS STEEL
9.	LOCK WASHER	18-8 STAINLESS STEEL
10.	O-RING	BUNA-N RUBBER
11.	LEVER ARM	316 STAINLESS STEEL
12.	FLOAT ARM	316 STAINLESS STEEL
13.	SPRING PIN	18-8 STAINLESS STEEL
14.	VALVE LINK	316 STAINLESS STEEL
15.	FLOAT PIVOT LINK	316 STAINLESS STEEL
16.	COVER BOLTS	316 STAINLESS STEEL
17.	PIPE PLUG, 1/2"	316 STAINLESS STEEL
18.	FLOAT ROD	316 STAINLESS STEEL
19.	FLOAT BALL	316 STAINLESS STEEL
20.	PIPE PLUG, 1"	316 STAINLESS STEEL
21.	PIPE PLUG, 2"	316 STAINLESS STEEL

FIGURE NUMBER	ORIFICE DIAMETER	WORKING PRESSURE
<b>925SS-L</b>	5/16" (7,9mm)	10-75 PSI (69-517KPa)
<b>925SS</b>	3/16" (4,8mm)	10-150 PSI (69-1034KPa)
<b>925SS-H</b>	1/8" (3,2mm)	10-300 PSI (69-2068 KPa)

INLET	OUTLET	A	B	C	WGT
2" NPT 3" NPT	1/2" NPT	6.38" (162mm)	20.50" (521mm)	4.50" (114mm)	60 lbs (27,3 kg)

<b>GA INDUSTRIES, a VAG Brand</b>		
DATE: 8-23-08	DRAWN BY: WJN	
<b>STAINLESS STEEL SEWAGE AIR RELEASE VALVE</b>		
<b>FIGURE 925SS</b>		DRAWING NO. <b>EAR-7008S-W</b>
		REV <b>A</b>