



**PARTS LIST**

ITEM	DESCRIPTION	MATERIAL
1.	BODY	CAST IRON, ASTM A126-B
2.	COVER	CAST IRON, ASTM A126-B
3.	LEVERAGE BRACKET	316 STAINLESS STEEL
4.	ORIFICE	316 STAINLESS STEEL
5.	LEVERAGE BRACKET SCREWS	18-8 STAINLESS STEEL
6.	BRACKET LOCK WASHER	18-8 STAINLESS STEEL
7.	ORIFICE BUTTON	BUNA-N / 18-8 STAINLESS STEEL
8.	HEX NUT	18-8 STAINLESS STEEL
9.	LOCK WASHER	18-8 STAINLESS STEEL
10.	O-RING	BUNA-N RUBBER
11.	LEVER ARM	316 STAINLESS STEEL
12.	FLOAT ARM	316 STAINLESS STEEL
13.	SPRING PIN	18-8 STAINLESS STEEL
14.	VALVE LINK	316 STAINLESS STEEL
15.	FLOAT PIVOT LINK	316 STAINLESS STEEL
16.	COVER BOLTS	A307 STEEL (Standard) 316 STAINLESS STEEL (Optional)
17.	PIPE PLUG, 1/2"	STEEL
18.	FLOAT ROD	316 STAINLESS STEEL
19.	FLOAT BALL	316 STAINLESS STEEL
20.	PIPE PLUG, 1"	MALLEABLE IRON
21.	PIPE PLUG, 2"	MALLEABLE IRON

INLET	OUTLET	A	B	C	WGT
2" NPT	1/2" NPT	6.38" (162mm)	20.50" (521mm)	4.50" (114mm)	60 lbs (27,3 kg)

FIGURE NUMBER	ORIFICE DIAMETER	WORKING PRESSURE
<b>925-L</b>	5/16" (7,9mm)	10-75 PSI (69-517KPa)
<b>925</b>	3/16" (4,8mm)	10-150 PSI (69-1034KPa)

**GA INDUSTRIES, a VAG Brand**

DATE: 8-23-08      DRAWN BY: WJN

**SEWAGEAIR RELEASE VALVE**

**FIGURE 925**

DRAWING NO. **EAR-7008-W**      REV **A**