



PARTS LIST

ITEM	DESCRIPTION	MATERIAL
1.	BODY	CAST IRON, ASTM A126-B*
2.	COVER	CAST IRON, ASTM A126-B*
3.	LEVERAGE BRACKET	316 STAINLESS STEEL
4.	ORIFICE	316 STAINLESS STEEL
5.	LEVERAGE BRACKET SCREWS	18-8 STAINLESS STEEL
6.	BRACKET LOCK WASHER	18-8 STAINLESS STEEL
7.	ORIFICE BUTTON	BUNA-N / 18-8 STAINLESS STEEL
8.	HEX NUT	18-8 STAINLESS STEEL
9.	LOCK WASHER	18-8 STAINLESS STEEL
10.	O-RING	BUNA-N RUBBER
11.	LEVER ARM	316 STAINLESS STEEL
12.	FLOAT ARM	316 STAINLESS STEEL
13.	SPRING PIN	18-8 STAINLESS STEEL
14.	VALVE LINK	316 STAINLESS STEEL
15.	FLOAT PIVOT LINK	316 STAINLESS STEEL
16.	COVER BOLTS	A307 STEEL, ZINC PLATED (OPTIONAL 316SS)
17.	PIPE PLUG, 1/2"	STEEL
18.	FLOAT ROD	316 STAINLESS STEEL
19.	FLOAT BALL	316 STAINLESS STEEL
20.	PIPE PLUG, 1"	MALLEABLE IRON
21.	PIPE PLUG, 2"	MALLEABLE IRON

* LINED AND COATED WITH NSF-61 CERTIFIED EPOXY

INLET	OUTLET	A	B	C	WGT
2" NPT	1/2" NPT	6.38" (162mm)	20.50" (521mm)	4.50" (114mm)	60 lbs (27,3 kg)

FIGURE NUMBER	ORIFICE DIAMETER	WORKING PRESSURE
925-L	5/16" (7,9mm)	10-75 PSI (69-517KPa)
925	3/16" (4,8mm)	10-150 PSI (69-1034KPa)

GA INDUSTRIES a +GF+ Brand		
DATE: 8-23-08	DRAWN BY: WJN	
SEWAGE AIR RELEASE VALVE		
FIGURE 925	DRAWING NO. EAR-7008W	REV B