



**PARTS LIST**

ITEM	DESCRIPTION	MATERIAL
1.	BODY	CAST IRON, ASTM A126-B*
2.	COVER	CAST IRON, ASTM A126-B*
3.	GASKET	ARMSTRONG CS-301
4.	ORIFICE	316 STAINLESS STEEL
5.	FLOAT ARM	316 STAINLESS STEEL
6.	LEVERAGE BRACKET	316 STAINLESS STEEL
7.	ORIFICE BUTTON	BUNA-N RUBBER
8.	SPRING PIN	302 STAINLESS STEEL
9.	FLOAT BALL	316 STAINLESS STEEL
10.	FLOAT SCREW	18-8 STAINLESS STEEL
11.	LOCK WASHER	18-8 STAINLESS STEEL
12.	PIPE PLUG, 1/2"	STEEL
13.	COVER BOLT	STEEL, ASTM A307 (OPTIONAL 316SS)
14.	SPIROL PIN	302 STAINLESS STEEL
15.	REDUCING BUSHING (Note 1)	STEEL
16.	PIPE PLUG, 1/4"	STEEL

\* LINED AND COATED WITH NSF-61 EPOXY

NOTE 1 - PART 15 USED IN 1/2" AND 3/4" SIZE ONLY

FIGURE NUMBER	ORIFICE DIAMETER	WORKING PRESSURE	PRESSURE RATING	WEIGHT
<b>905</b>	0.094"	10-150 PSI	200 PSI.	5 LBS.
<b>905-H</b>	0.063"	10-200 PSI		

FIGURE 905 AIR RELEASE VALVES ARE MANUFACTURED AND TESTED IN ACCORDANCE WITH AWWA C512

<b>GA INDUSTRIES</b> a +GF+ Brand			
DATE:	1-24-09	DRAWN BY:	WJN
<b>SIMPLE LEVER AIR RELEASE VALVE</b>			
<b>FIGURES 905, 905H</b>			DRAWING NO. <b>EAR-7010-W</b>
			REV <b>A</b>