



PARTS LIST

Part	Name	Material
1	Figure 930 Air & Vacuum Valve	6" to 8" - Drawing EAV-7049-W 10" to 12" - Drawing EAV-7050-W
2	Figure F284 Surge Check Valve	Drawing C-7029-W
3	Bolt	Steel, ASTM A307 (Optional 316SS)
4	Nut	Steel, ASTM A307 (Optional 316SS)
5	Gasket	Composition

SIZE	A	B	WEIGHT
6"	15-1/4"	30-1/2"	250 lbs
8"	19"	37-3/4"	470 lbs
10"	23-1/2"	47-1/4"	675 lbs
12"	27-1/2"	51-3/4"	945 lbs

FIGURE NUMBER	INLET FLANGE	OUTLET	MAXIMUM WORKING PRESSURE	PRESSURE RATING	HYDRO TEST PRESSURE
931-DC	ANSI CLASS 125	Cowl	150 PSI	150 PSI	225 PSI

FIGURE 931 AIR & VACUUM
VALVES ARE
MANUFACTURED AND
TESTED IN ACCORDANCE
WITH AWWA C512

GA INDUSTRIES A VAG Group Brand			
DATE:	1-17-09	DRAWN BY:	WJN
6" to 12" SLOW-CLOSING AIR VACUUM VALVE WITH SURGE CHECK			
Figures 931-DC			DRAWING NO. EAV-7245-W
			REV A