



PARTS LIST

ITEM	DESCRIPTION	MATERIAL
1.	BODY	316 STAINLESS STEEL
2.	COVER	316 STAINLESS STEEL
3.	LEVERAGE BRACKET	316 STAINLESS STEEL
4.	ORIFICE	316 STAINLESS STEEL
5.	BRACKET SCREWS	18-8 STAINLESS STEEL
6.	BRACKET LOCK WASHER	410 STAINLESS STEEL
7.	ORIFICE BUTTON	BUNA-N / 18-8 STAINLESS STEEL
8.	HEX NUT	18-8 STAINLESS STEEL
9.	LOCK WASHER	410 STAINLESS STEEL
10.	O-RING	BUNA-N RUBBER
11.	LEVER ARM	316 STAINLESS STEEL
12.	FLOAT ARM	316 STAINLESS STEEL
13.	SPRING PIN	316 STAINLESS STEEL
14.	AIR RELEASE VALVE LINK	316 STAINLESS STEEL
15.	PIVOT LINK	316 STAINLESS STEEL
16.	COVER BOLTS	316 STAINLESS STEEL
17.	PIPE PLUG, 1/2"	316 STAINLESS STEEL
18.	PIPE PLUG, 1"	316 STAINLESS STEEL
19.	PIPE PLUG, 2"	316 STAINLESS STEEL
20.	FLOAT BALL	316 STAINLESS STEEL
21.	FLOAT ROD	316 STAINLESS STEEL

INLET	OUTLET	A	B	C	WGT
2" NPT 3" NPT	1/2" NPT	6.38" (162mm)	12.00" (305mm)	4.50" (115mm)	40 lbs (18,1 kg)

FIGURE NUMBER	ORIFICE DIAMETER	WORKING PRESSURE
929SS-L	5/16" (7,9mm)	10-150 PSI (69-517 KPa)
929SS	3/16" (4,8mm)	10-150 PSI (69-1034KPa)

GA INDUSTRIES a +GF+ Brand

DATE: 8-18-08	DRAWN BY: WJN
DUROVENT™ ALL STAINLESS STEEL SHORT BODY SEWAGE AIR RELEASE VALVE	
FIGURE 929SS	DRAWING NO. EAV-7004S-W
	REV A