



**PARTS LIST**

ITEM	DESCRIPTION	MATERIAL
1.	BODY	CAST IRON, ASTM A126-B*
2.	COVER	CAST IRON, ASTM A126-B*
3.	LEVERAGE BRACKET	316 STAINLESS STEEL
4.	ORIFICE	316 STAINLESS STEEL
5.	BRACKET SCREWS	18-8 STAINLESS STEEL
6.	BRACKET LOCK WASHER	410 STAINLESS STEEL
7.	ORIFICE BUTTON	BUNA-N / 18-8 STAINLESS STEEL
8.	HEX NUT	18-8 STAINLESS STEEL
9.	LOCK WASHER	410 STAINLESS STEEL
10.	O-RING	BUNA-N RUBBER
11.	LEVER ARM	316 STAINLESS STEEL
12.	FLOAT ARM	316 STAINLESS STEEL
13.	SPRING PIN	316 STAINLESS STEEL
14.	AIR RELEASE VALVE LINK	316 STAINLESS STEEL
15.	PIVOT LINK	316 STAINLESS STEEL
16.	COVER BOLTS	A307 STEEL, ZINC PLATED (OPTIONAL 316SS)
17.	PIPE PLUG, 1/2"	STEEL
18.	PIPE PLUG, 1"	CAST IRON
19.	PIPE PLUG, 2"	MALLEABLE IRON
20.	FLOAT BALL	316 STAINLESS STEEL
21.	FLOAT ROD	316 STAINLESS STEEL

\* LINED AND COATED WITH NSF-61 CERTIFIED EPOXY

INLET	OUTLET	A	B	C	WGT
2" NPT 3" NPT	1/2" NPT	6.38" (162mm)	12.00" (305mm)	4.50" (115mm)	40 lbs (18,1 kg)

FIGURE NUMBER	ORIFICE DIAMETER	WORKING PRESSURE
<b>929-L</b>	5/16" (7,9mm)	10-150 PSI (69-517 KPa)
<b>929</b>	3/16" (4,8mm)	10-150 PSI (69-1034KPa)

<b>GA INDUSTRIES a +GF+ Brand</b>		
DATE: 8-18-08	DRAWN BY: WJN	
<b>SHORT BODY SEWAGE AIR RELEASE VALVE</b>		
<b>FIGURE 929</b>	DRAWING NO. <b>EAV-7004-W</b>	REV <b>A</b>