



**PARTS LIST**

ITEM	DESCRIPTION	MATERIAL
1.	BODY	CAST IRON, ASTM A126-B
2.	COVER	CAST IRON, ASTM A126-B
3.	SEAT	BUNA-N & 304 STAINLESS STEEL
4.	COVER BOLTS	ZINC PLATED STEEL (Standard)
		316 STAINLESS STEEL (Optional)
5.	FLOAT BALL	316 STAINLESS STEEL
6.	PIPE PLUG	STEEL
7.	CUSHION	BUNA-N RUBBER
8.	COVER NUTS	ZINC PLATED STEEL (Standard)
		316 STAINLESS STEEL (Optional)
9.	COWL	STEEL
10.	COWL BOLTS	ZINC PLATED STEEL (Standard)
		316 STAINLESS STEEL (Optional)
11.	COWL WASHER	ZINC PLATED STEEL (Standard)
		316 STAINLESS STEEL (Optional)
12.	FLOAT GUIDE	316 STAINLESS STEEL
13.	GUIDE BEARING	LOW FRICTION POLYMER

FIGURE NUMBER	FLANGE CLASS	MAX WORKING PRESSURE	HYDRO TEST PRESSURE
<b>930-DC</b>	ANSI B16.1 CLASS 125	200 PSI (1,379KPa)	300 PSI (2,068 KPa)
<b>930-UT</b>	ANSI B16.1 CLASS 250	300 PSI (2,068 KPa)	450 PSI (3,102 KPa)

FIGURE 930 AIR & VACUUM VALVES ARE MANUFACTURED AND TESTED IN ACCORDANCE WITH AWWA C512

SIZE	INLET	A	B	WGT
6" (DN150)	6" FLANGE	15.25" (387mm)	20.75" (527mm)	175 lbs (80 kg)
8" (DN200)	8" FLANGE	19.00" (483mm)	25.25" (641mm)	335 lbs. (152 kg)

<b>GA INDUSTRIES, a VAG Brand</b>			
DATE:	8-23-08	DRAWN BY:	WJN
<b>6" &amp; 8" KINETIC AIR &amp; VACUUM VALVE</b>			
<b>FIGURE 930</b>		DRAWING NO.	REV
		<b>EAV-7049-W</b>	<b>B</b>