



PARTS LIST		
ITEM	DESCRIPTION	MATERIAL
1.	BODY	CAST IRON, ASTM A126-B*
2.	COVER	CAST IRON, ASTM A126-B*
3.	SEAT	BUNA-N & STAINLESS STEEL
4.	COVER BOLTS	ASTM A307 ZINC PLATED STEEL (OPTIONAL 316 SS)
5.	FLOAT BALL	316 STAINLESS STEEL
6.	PIPE PLUG	STEEL
7.	CUSHION	BUNA-N
8.	COVER NUTS	ASTM A307 ZINC PLATED STEEL (OPTIONAL 316 SS)
9.	COWL	STEEL
10.	COWL BOLTS	ASTM A307 ZINC PLATED STEEL (OPTIONAL 316 SS)
11.	COWL WASHER	ZINC PLATED STEEL (OPTIONAL 316 SS)
12.	FLOAT GUIDE	316 STAINLESS STEEL
13.	GUIDE BEARING	SELF LUBRICATING POLYMER

* LINED AND COATED WITH NSF-61 CERTIFIED EPOXY

FIGURE NUMBER	INLET	OUTLET	WORKING PRESSURE	HYDRO TEST PRESSURE
930-DC	ANSI B16.1 CLASS 125	COWL	10-200 PSI	300 PSI
930-DJ	ANSI B16.1 CLASS 125	ANSI B16.1 CLASS 125		
930-UC	ANSI B16.1 CLASS 250	COWL	10-300 PSI	450 PSI
930-UJ	ANSI B16.1 CLASS 250	ANSI B16.1 CLASS 125		

FIGURE 930 AIR & VACUUM VALVES ARE MANUFACTURED AND TESTED IN ACCORDANCE WITH AWWA C512

SIZE	A	B	BB*	WGT
6"	15¼"	20¾"	18"	175 lbs.
8"	19"	25½"	20½"	335 lbs.

* DIMENSION BB IS HEIGHT WITH FLANGED OUTLET (NO COWL)

GA INDUSTRIES a +GF+ Brand		
DATE:	8-23-08	DRAWN BY: WJN
6" & 8" KINETIC AIR & VACUUM VALVE		
FIGURE 930		DRAWING NO. EAV-7049-W REV C