



PARTS LIST		
ITEM	DESCRIPTION	MATERIAL
1.	BODY	CAST IRON, ASTM A126-B
2.	COVER	CAST IRON, ASTM A126-B
3.	SEAT	BUNA-N RUBBER
4.	FOLLOWER RING	316 STAINLESS STEEL
5.	SEAT SCREWS	18-8 STAINLESS STEEL
6.	O-RING	BUNA-N RUBBER
7.	COVER BOLTS	ZINC PLATED STEEL (Standard)
		316 STAINLESS STEEL (Optional)
8.	CUSHION	BUNA-N RUBBER
9.	FLOAT GUIDE	316 STAINLESS STEEL
10.	FLOAT BALL	316 STAINLESS STEEL
11.	PIPE PLUG	MALLEABLE IRON
12.	COWL	STEEL
13.	COVER NUTS	ZINC PLATED STEEL (Standard)
		316 STAINLESS STEEL (Optional)
14.	COWL BOLTS	ZINC PLATED STEEL (Standard)
		316 STAINLESS STEEL (Optional)
15.	COWL WASHER	ZINC PLATED STEEL (Standard)
		316 STAINLESS STEEL (Optional)
16.	GUIDE BEARING	LOW FRICTION POLYMER

FIGURE NUMBER	FLANGE CLASS	SIZES	MAX WORKING PRESSURE	HYDRO TEST PRESSURE
<b>930-DC</b>	ANSI B16.1 CLASS 125	10" & 12"	200 PSI (1,379 KPa)	300 PSI (2,068, KPa)
<b>930-UC</b>	ANSI B16.1 CLASS 250	10" & 12"	300 PSI (2,068 KPa)	450 PSI (3,102 KPa)

SIZE	10" (DN250)	12" (DN300)
A	23.50" (570 mm)	27.50" (699 mm)
B	33.00" (838 mm)	39.88" (1,013 mm)
WGT	475 lbs (216 kg)	625 lbs (284 kg)

FIGURE 930 AIR & VACUUM VALVES ARE MANUFACTURED AND TESTED IN ACCORDANCE WITH AWWA C512

**GA INDUSTRIES, a VAG Brand**

DATE: 8-26-08	DRAWN BY: WJN
<b>10" &amp; 12" KINETIC AIR &amp; VACUUM VALVE</b>	
<b>FIGURE 930</b>	DRAWING NO. <b>EAV-7050-W</b>
	REV <b>B</b>