



PARTS LIST

ITEM	DESCRIPTION	MATERIAL
1.	BODY	CAST IRON, ASTM A126-B*
2.	COVER	CAST IRON, ASTM A126-B*
3.	SEAT	BUNA-N RUBBER
4.	FOLLOWER RING	316 STAINLESS STEEL
5.	SEAT SCREWS	18-8 STAINLESS STEEL
6.	O-RING	BUNA-N RUBBER
7.	COVER BOLTS	ASTM A307 ZINC PLATED STEEL (OPTIONAL 316 SS)
8.	CUSHION	BUNA-N RUBBER
9.	FLOAT GUIDE	316 STAINLESS STEEL
10.	FLOAT BALL	316 STAINLESS STEEL
11.	PIPE PLUG	MALLEABLE IRON
12.	COWL	STEEL*
13.	COVER NUTS	ASTM A307 ZINC PLATED STEEL (OPTIONAL 316 SS)
14.	COWL BOLTS	ASTM A307 ZINC PLATED STEEL (OPTIONAL 316 SS)
15.	COWL WASHER	ZINC PLATED STEEL (OPTIONAL 316 SS)
16.	GUIDE BEARING	SELF LUBRICATING POLYMER

* LINED AND COATED WITH NSF-61 CERTIFIED EPOXY

FIGURE NUMBER	INLET	OUTLET	WORKING PRESSURE	HYDRO TEST PRESSURE
930-DC	ANSI B16.1 CLASS 125	COWL	10-200 PSI	300 PSI
930-DJ	ANSI B16.1 CLASS 125	ANSI B16.1 CLASS 125	10-200 PSI	300 PSI
930-UC	ANSI B16.1 CLASS 250	COWL	10-300 PSI	450 PSI
930-UJ	ANSI B16.1 CLASS 250	ANSI B16.1 CLASS 125	10-300 PSI	450 PSI

FIGURE 930 AIR & VACUUM VALVES ARE MANUFACTURED AND TESTED IN ACCORDANCE WITH AWWA C512

GA INDUSTRIES a +GF+ Brand		
DATE: 8-26-08	DRAWN BY: WJN	
10" and 12" KINETIC AIR & VACUUM VALVE		
FIGURE 930-D, 930-U		DRAWING NO. EAV-7050W REV A

SIZE	A	B	BB*	WEIGHT, LBS.	
				CL125	CL250
10"	23½"	33"	27"	475	510
12"	27½"	39½"	32½"	625	725

* DIMENSION BB IS HEIGHT TO CLASS 125 FLANGED OUTLET CONNECTION (NO COWL)