



### PARTS LIST

ITEM	DESCRIPTION	MATERIAL
1.	BODY	CAST IRON, ASTM A126-B*
2.	COVER	CAST IRON, ASTM A126-B*
3.	SEAT	BUNA-N & 304 STAINLESS STEEL
4.	COVER BOLTS	ASTM A307 ZINC PLATED STEEL (OPTIONAL 316SS)
5.	COVER NUTS	ASTM A307 ZINC PLATED STEEL (OPTIONAL 316SS)
6.	REDUCING BUSHING	STEEL (USED ONLY ON 1/2" AND 3/4" SIZES)
7.	PIPE PLUG	STEEL
8.	FLOAT BALL	316 STAINLESS STEEL
9.	FLOAT GUIDE	ULTRA HIGH MOLECULAR WEIGHT POLYETHYLENE
10.	CUSHION	BUNA-N RUBBER
11.	GUIDE BEARING	SELF LUBRICATING POLYMER
12.	PIPE PLUG	STEEL

\* LINED AND COATED WITH NSF-61 CERTIFIED EPOXY

FIGURE NUMBER	MAXIMUM WORKING PRESSURE	HYDRO TEST PRESSURE	WEIGHT
<b>930-T</b>	300 PSI	450 PSI	10 LBS.

FIGURE 930 AIR & VACUUM VALVES ARE MANUFACTURED AND TESTED IN ACCORDANCE WITH AWWA C512

<b>GA INDUSTRIES</b> a +GF+ Brand			
DATE:	8-23-08	DRAWN BY:	WJN
<b>1/2", 3/4" &amp; 1" KINETIC AIR &amp; VACUUM VALVE</b>			
<b>FIGURE 930-T</b>		DRAWING NO.	REV
		<b>EAV-7051W</b>	<b>A</b>