



**PARTS LIST**

ITEM	DESCRIPTION	MATERIAL
1.	BODY	CAST IRON, ASTM A126-B
2.	COVER	CAST IRON, ASTM A126-B
3.	SEAT	BUNA-N & 304 STAINLESS STEEL
4.	COVER BOLTS	ZINC PLATED STEEL (Standard)
		316 STAINLESS STEEL (Optional)
5.	FLOAT BALL	316 STAINLESS STEEL
6.	PIPE PLUG	STEEL
7.	COVER NUTS	ZINC PLATED STEEL (Standard)
		316 STAINLESS STEEL (Optional)
8.	FLOAT GUIDE	ULTRA HIGH MOLECULAR WEIGHT POLYETHYLENE
9.	CUSHION	EPDM RUBBER
10.	GUIDE BEARING	LOW FRICTION POLYMER

FIGURE NUMBER	MAXIMUM WORKING PRESSURE	HYDRO TEST PRESSURE
<b>930-T</b>	300 PSI (2,068 KPa)	450 PSI (3,103 KPa)

FIGURE 930 AIR & VACUUM VALVES ARE MANUFACTURED AND TESTED IN ACCORDANCE WITH AWWA C512

SIZE	INLET	OUTLET	A	B	C	WGT
2" (DN50)	2" NPT	2" NPT	5.38" (137mm)	8.38" (213mm)	3.62" (92mm)	20 lbs (9,1 kg)
3" (DN80)	3" NPT	3" NPT	6.63" (168mm)	10.63" (270mm)	4.13" (105mm)	30 lbs (13,4 kg)

**GA INDUSTRIES, a VAG Brand**

DATE: 8-23-08	DRAWN BY: WJN	
<b>2" &amp; 3" KINETIC AIR &amp; VACUUM VALVE</b>		
<b>FIGURE 930-T</b>		DRAWING NO. <b>EAV-7052-W</b> REV <b>B</b>