



PARTS LIST

ITEM	DESCRIPTION	MATERIAL
1.	BODY	CAST IRON, ASTM A126-B*
2.	COVER	CAST IRON, ASTM A126-B*
3.	SEAT	BUNA-N & 304 STAINLESS STEEL
4.	COVER BOLTS	ASTM A307 ZINC PLATED STEEL (OPTIONAL 316SS)
5.	FLOAT BALL	316 STAINLESS STEEL
6.	PIPE PLUG	STEEL
7.	COVER NUTS	ASTM A307 ZINC PLATED STEEL (OPTIONAL 316SS)
8.	FLOAT GUIDE	ULTRA HIGH MOLECULAR WEIGHT POLYETHYLENE
9.	CUSHION	BUNA-N
10.	GUIDE BEARING	SELF LUBRICATING POLYMER

* LINED AND COATED WITH NSF-61 CERTIFIED EPOXY

FIGURE NUMBER	MAXIMUM WORKING PRESSURE	HYDRO TEST PRESSURE
930-T	300 PSI	450 PSI

FIGURE 930 AIR & VACUUM VALVES ARE MANUFACTURED AND TESTED IN ACCORDANCE WITH AWWA C512

GA INDUSTRIES <i>a +GF+ Brand</i>		
DATE: 8-23-08	DRAWN BY: WJN	
2" & 3" KINETIC AIR & VACUUM VALVE		
FIGURE 930-T	DRAWING NO. EAV-7052-W	REV C

SIZE	INLET	OUTLET	A	B	C	WGT
2"	2" NPT	2" NPT	5 ³ / ₈ "	8 ¹ / ₄ "	3 ⁵ / ₈ "	20 lbs.
3"	3" NPT	3" NPT	6 ⁵ / ₈ "	10 ⁵ / ₈ "	4 ¹ / ₂ "	40 lbs.