



PARTS LIST

ITEM	DESCRIPTION	MATERIAL
1.	BODY	CAST IRON, ASTM A126-B*
2.	COVER	CAST IRON, ASTM A126-B*
3.	SEAT	BUNA-N
4.	COVER BOLTS	ASTM A307 ZINC PLATED STEEL (OPTIONAL 316SS)
5.	FLOAT BALL	316 STAINLESS STEEL
6.	PIPE PLUG	STEEL
7.	COVER NUTS	ASTM A307 ZINC PLATED STEEL (OPTIONAL 316SS)
8.	FLOAT GUIDE	ULTRA HIGH MOLECULAR WEIGHT POLYTHYLENE
9.	CUSHION	BUNA-N
10.	GUIDE BEARING	SELF LUBRICATING POLYMER

* LINED AND COATED WITH NSF-61 CERTIFIED EPOXY

FIGURE NUMBER	INLET	OUTLET	MAXIMUM WORKING PRESSURE	HYDRO TEST PRESSURE	WEIGHT
930-DT	4" ANSI B16.1 CLASS 125	4" NPT	200 PSI	300 PSI	85 LBS.
930-UT	4" ANSI B16.1 CLASS 250	4" NPT	300 PSI	450 PSI	95 LBS.

FIGURE 930 AIR & VACUUM VALVES ARE MANUFACTURED AND TESTED IN ACCORDANCE WITH AWWA C512

GA INDUSTRIES a +GF+ Brand		
DATE: 8-23-08	DRAWN BY: WJN	
4" KINETIC AIR & VACUUM VALVE		
DRAWING NO. FIGURES 930-DT, 930-UT		REV C
EAV-7053-W		