



NO.	DESCRIPTION
1	BODY
2	BODY SEAT
2A	BODY SEAT PINS
2B	BODY SEAT O-RING
3	DISC
3A	DISC CENTER PIN
4	DISC ARM
5A	SEAT RING
5B 5C	SEAT FOLLOWER SEAT FOLLOWER SCREWS
6	DISC NUT
6A	DISC NUT WASHER
6B	DISC NUT COTTER PIN
8	COVER GASKET
9	COVER
10	COVER BOLTS
11	SHAFT
12	DISC ARM SET SCREW
13	INNER BUSHING
14	OUTER BUSHING
15 16	GLAND STUDS
10	GLAND STUDS GLAND PACKING
18	SHAFT LOCK PIN
20	CYLINDER
21	CUSHION CHAMBER BOLTS
22	PISTON
23A	PISTON SEAL
25	CYLINDER LINER
26	CHAMBER ADJUSTING SLEEVE
27 28	ADJUSTING SLEEVE LOCKNUT
	PISTON PIN
28	
29	LEVER
29A	LEVER SET SCREW
29E	B LEVER PIN
290	LEVER COTTER PINS
30	
30A	
30E	
300	COUNTERWEIGHT ARM
30L	
31	COUNTERWEIGHT
31A	
32	CHECK VALVE
33	ANTI-ROTATION PIN
34	ANTI-ROTATION PIN SCREWS
35	BLANK GLAND
36	BLANK GLAND STUDS
37	BLANK GLAND O-RING CUSH CHAMBER MT'G PLATE
38 39	CUSH CHAMBER MIG PLATE CUSHION CHAMBER MI'G PLATE BOLTS
59	COSTINGTY OF A WIDEN WIT OF LATE DUELS
L	•

J:\GA-VALVE\GA-SHOW\C-1346.DWG								
GA INDUSTRIES, INC.								
24" SWING CHECK VALVE WITH UPDATED CUSHION CHAMBER								
STANDARD TOLERANCES (UNLESS OTHERWISE NOTED)	SERIAL NO.	SCALE	DR	AWN BY	HGM			
Finished surfaces only	051511	NTS	AP	PR. BY	JJF			
DIMENSIONS SHOWN IN INCHES	DEEEDENOEO							
$.x = \pm .02$ $.xx = \pm .01$	REFERENCES	EFFECTIVE DATE	8-31-0	5 T	0			