



SIZE	A	B	C	D	E	F	BOLT SIZE	NO. OF BOLTS	G	H	J	K
2	8	4 3/4	6	5/8	2	3 3/8	5/8	4	1 1/2 ALL SIZES	1" ALL SIZES	7	0
2 1/2	8 1/2	5 1/2	7	11/16	2 1/2	3 3/8	5/8	4			7	0
3	9 1/2	6	7 1/2	3/4	3	5 1/8	5/8	4			8	0
4	11 1/2	7 1/2	9	15/16	4	5 3/4	5/8	8			8	2
6	15	9 1/2	11	1	6	6 7/8	3/4	8			13	2
8	19 1/2	11 3/4	13 1/2	1 1/8	8	8 3/8	3/4	8			17	3
10	24 1/2	14 1/4	16	1 3/16	10	10 3/4	7/8	12			20	4
12	27 1/2	17	19	1 1/4	12	12 1/2	7/8	12			23	4
14	31	18 3/4	21	1 3/8	14	13	1	12			27	4
16	32	21 1/4	23 1/2	1 7/16	16	14 1/4	1	16			31	5
18	36	22 3/4	25	1 9/16	18	15 1/4	1 1/8	16			34	6
20	40	25	27 1/2	1 11/16	20	16 7/8	1 1/8	20			38	6
24	48	28 1/2	32	1 7/8	24	19 1/4	1 1/4	20	45	7		

BILL OF MATERIALS			
No.	DESCRIPTION	QTY.	MATERIAL
1	BODY	1	DUCTILE IRON
2	COVER	1	DUCTILE IRON
3	DISC	1	RUBBER COATED STL
4	GASKET	1	NBR
5	COVER BOLTS	VARIABLES PER VALVE SIZE	SST
6	SPRING ASSIST	1	SST
7	SPRING ASSIST SUPPORT PLATE	1	SST
8	SPRING ASSIST SCREWS	2	SST
12	ROD WIPER	1	URETHANE RUBBER
13	ROD SEAL	1	BUNA-N RUBBER
14	BACKFLOW TUBE	1	BRASS
15	BACKFLOW JAM NUT	1	SST
16	BACKFLOW ROD	1	SST
17	BACKFLOW ROD HANDLE	1	SST
18	BACKFLOW ROD SET SCREW	1	SST

J:\AUTOCAD\GA-VALVE\GA-SHOW\C-1394-C.DWG

GA INDUSTRIES, LLC

2"-24" SPRING ASSISTED RUBBER FLAPPER SWING CHECK VALVE W/BACKFLOW ACTUATOR - 125# ANSI FLANGES

STANDARD TOLERANCES (UNLESS OTHERWISE NOTED) FINISHED SURFACES ONLY DIMENSIONS SHOWN IN INCHES .x = ±.02 .xx = ±.01 .xxx = ±.002 FRACTIONS ±1/64" ANGLES ±1' FINISH ⌀-XX RMS	SERIAL NO.	SCALE NONE	DRAWN BY SWR APPR. BY JT	
	REFERENCES	EFFECTIVE DATE 06-12-2009 TO	FIG. NUMBER SB200-DBF	REV. C
		FILE C	DRAWING NO. C-1394	REV. C

REV.	DESCRIPTION	DATE	BY
C	ADDED 2"-2 1/2" SIZES BACK TO TABLE	07-29-2014	SWR
B	ADDED 3" SIZE BACK TO TABLE	09-27-2011	SWR
A	ELIMINATED SIZES 2"-3" FROM TABLE	03-29-2011	SWR

AVAILABLE IN SIZES I AND III