

Figures 942, 942F Single Body Sewage Combination Air Valve

Description

GA Industries Figure 942 Combination Air Valves employ a large and small orifice in a single body to efficiently vent air and gas from sewage forcemains. Air is vented through the large orifice as the system is filled and then it closes tight once the system is full and pressurized. Residual air and gas is released through the small orifice while the system is in operation. The large orifice automatically opens to admit air when the forcemain is drained and/or a negative pressure occurs in the valve.

Figure 942 are typically installed at system high points where air and sewage gas naturally rise during filling, collect during operation and vacuum first forms during draining. The elongated body is designed to maintain an air gap between the solids bearing fluid and the valve's internal mechanism to minimize fouling and spillage.

Figure 942F includes optional "back flushing attachments" to facilitate cleaning sludge and debris from the valve



Product Features

- Full size large orifice for maximum air outflow and inflow rates
- Corrosion resistant Type 316 stainless steel float, plug, seat ring and internal mechanism
- Elongated body reduces potential for fouling
- Tight sealing and easily replaceable rubber seat
- 2" NPT plugged side port allows removal of large debris

Standard Materials

- Body & Cover Cast Iron, ASTM A126 Class B
- Float Stainless Steel, Type 316
- Internal Linkage Stainless Steel, Type 316
- Replaceable Seat Buna-N
- External Fasteners Steel, A307, Zinc Plated
- Coating Internal and External NSF-61 Certified Epoxy

Ordering Data

- Figure Number (942, 942F)
- Size (Inlet x Outlet)
- Options/Accessories

Approvals & Certifications

- Complies with AWWA Standard C512

Options/Accessories

- Option BA Build America/Buy America (BABA) and American Iron and Steel (AIS) Compliant
- Option CV Bronze surge check (regulated exhaust/slow closing device) installed in air valve outlet
- Option FA: Backflush Attachments – inlet isolating valve, 1/2" flushing valve, 1" blow off valve, quick connect couplings and 5 ft. rubber hose
- Option IV Inlet Isolating Valve – lever operated bronze ball valve (inlet isolating valve included with backflush attachments.
- Option SE 316 stainless steel external fasteners
- Option US American Iron and Steel (AIS) Compliant

Non-Shock Working Water Pressure at up to 150F (66C)									
	Valve Only					Valve and Backflush Attachments*			
Figure Numbers	942					942F			
Valve Size	2" x 1"	2"	3" x 2"	3"	4"	2" x 1"	2"	3" x 2"	3"
Inlet Size	2" NPT	2" NPT	3" NPT	3" NPT	4" NPT	2" NPT	2" NPT	3" NPT	3" NPT
Outlet Size	1" NPT	2" NPT	2" NPT	3" NPT	4" NPT	1" NPT	2" NPT	2" NPT	3" NPT
Working Pressure	10-150 PSI					10-150 PSI			
Pressure Rating	200 PSI					200 PSI			
Hydro Test	300 PSI					300 PSI			

* See Data Sheet 942.02 for 4" and 6" flanged valves with backflush attachments

Data Sheet 942.01H

Air Vacuum Orifice

Pressure at Valve Inlet	Air Outflow Rate, Standard Cubic Feet/Min (SCFM)				
	2" x 1"	2"	3" x 2"	3"	4"
1 PSI	78	279	279	706	1208
2 PSI	114	407	407	1031	1762
3 PSI	144	513	513	1300	2222
4 PSI	171	609	609	1543	2637
5 PSI	196	699	699	1770	3027

Value is rate at which air is vented from pipeline/system during filling at valve inlet pressures shown. Inlet pressure during filling should not exceed 2 PSI. Size is inlet x outlet.

Air Vacuum Orifice

Pressure at Valve Inlet	Air Inflow Rate, Standard Cubic Feet/Min (SCFM)				
	2" x 1"	2"	3" x 2"	3"	4"
-1 PSIG	79	318	318	717	1275
-2 PSIG	112	451	451	1015	1804
-3 PSIG	138	552	552	1243	2210
-4 PSIG	159	637	637	1435	2551
-5 PSIG	178	713	713	1604	2853

Value is rate at which air is drawn into the valve at negative pipeline/system pressure shown. Size is inlet x outlet.

Air Release Orifice

Pressure At Valve Inlet	Air Release Orifice Venting Rate, Standard Cubic Feet/Min (SCFM)	
	2" x 1", 2" and 3" x 2"	3" and 4"
10 PSI	3.9	8.7
15 PSI	4.7	10.6
25 PSI	6.3	14.1
50 PSI	10.3	23.1
75 PSI	14.2	32.0
100 PSI	18.2	40.9
150 PSI	26.1	58.7

Installation Dimensions

SIZE	2'x1", 2"	3" x 2"	3"	4"
A (Square)	6½"	6½"	9½"	13½"
B	20½"	20½"	23½"	25½"
C	4½"	4½"	7"	7"
D	5"	8"	8"	NA
E	8"	13"	13"	NA
F	10"	10"	12"	NA
Valve Weight	60 lb.	60 lbs.	170 lb.	190 lbs.
Add for Inlet Isolating Valve Only	8 lbs.	20 lbs.	20 lbs.	Not Available*
Add for Backflush Attachments	15 lbs.	27 lbs.	27 lbs.	Not Available*

* For 4" valves with inlet isolating valve or backflush attachments, see Data Sheet 942.02
All dimensions and weights are approximate. If critical request certified drawings

